DEFENDER Outdoor LED Wallpack











PERFORMANCE SUMMARY

The slim modern design of the Defender Series LED fits well in any residential and commercial building style, with even a built in photocell that automatically turns the light on at dusk and off at dawn.

It's compact and efficient consuming 80% less energy than a $100\ MH$ wall pack.

Features

- Standard photo cell for dusk to dawn operation
- Exceptional operating efficiency of 110lm/W
- High impact polyester housing and polycarbonate diffuser with IP65 weather protection rating
- Fully gasketed polycarbonate lens provides and even light distribution and protects electronics
- Aesthetically designed profile compliments both residential and commercial settings
- Replaces up to 70W HPS or 100W MH
- High powered LEDs provide 2200 or 3300 lumens at neutral 4000°K

Specification

Volts: AC100-277V

Average Rated Life: 50,000hrs

CRI: RA80 Beam Angle: 120°


Environment Location: IP65

Weight: 2.6lbs

Ambient Temp: -20°C to 50°C Sensor Range: 4.5-14Fc





PHOTOMETRICS



DIMENSIONS

Weight (May vary with accessories) 3.7lbs (1.67kg)





PRODUCT CODE

Example Defender cat. 20.3.B.12.PC

Model No	Wattage	CCT (°K)	Finish	Distribution	Options
Defender	20 - 20W/2,200lms	3 - 3000	B - Bronze	12 -120°	0 - None
	30 - 30W/3,300Ims	4 - 4000			PC - Photocell
		57 - 5700			

