# SLATE MOD/2 Direct/Indirect Wallpack









**Applications:** Building perimeters, residential courtyards, exterior security, building facades, pathway and perimeter lighting

### PERFORMANCE SUMMARY

Whether you are trying to meet specification, code, or seeking a building mount solution with the right options, the Slate LED was designed to provide elegant wall-mounted lighting solutions for building perimeter applications

With clean square lines, it blends seamlessly into any architecture, meeting the everyday lighting needs of engineers and architects alike. The Slate comes in both in up or down distributions and 600 to 4,000 lumens packages

### Construction

- Durable extruded heavy duty die cast aluminium housing
- Surface finished with a proprietary Akzo Nobel treatment, withstanding harsh weather conditions without cracking or peeling

## Optical

- Available in T3 symmetric or T4 asymmetric distribution options for facade or area illumination applications
- Dark sky friendly with minimal uplight of less than 5% total lumen output illuminating above 900 (down only model)
- Tempered glass lens
- Long life aluminium LED COB with added corrision resistance for enhancing protection against moisture and contaminants
- Delivered lighting output up to 4,000 median lumens
- Easy installation with threaded conduit holes on back of fixture

## Electrical

- Long life drivers up to L70/80,000 hours at 77°F
- Class 2 high efficiency LED driver, with a optional 1-10V dimming
- Wide range input voltage AC100-277V 0-10V dimmable


### **Specification**


Volts: AC100-240V MacAdam Step: SDCM < 5 Average Rated Life: 60,000hrs Dimming: 0-10V

CRI: > RA80


**Environment Location: IP65** Ambient Temp: -4°F to 122°F


## **PHOTOMETRICS** Type 3 (T3)






Type 4 (T4)






# **DIMENSIONS**

Weight: (May vary with accessories) 6.6lbs (3.0kg)







## PRODUCT CODE

Example Slate cat. 1.C06.1.T3.27.B.M

Model No	Beam Angle	Wattage (W)	Distribution	CCT (°K)	Housing Color	Accessories
Slate	1 - Up or Down	C06.1 - 6W x1/600lm x1 C20.1 - 20W x1/2000lm x1	T3 - Type 3 T4 - Type 4	27 - 2700 30 - 3000	B - Black RAL9011	EM - 8W/90min Emergency
	2 - Up and Down	C06.2 - 6W x2/600lm x2 C20.2 - 20W x2/2000lm x2	тч - туре ч	40 - 4000 60 - 6000	W - White RAL9016	M - Marine resistance
					G - Gray RAL7012	DIM - 0-10V dimming
					M - Mineral Bronze	0 - None
SUNLED					S - Silver RAL9006	